



Series T, LT – Two Stage Infrared Tube Heaters

Part #	Features	Specification
 <p>Part # - CE211</p>	<ul style="list-style-type: none"> ✓ Compatible with heat pumps, gas or electric systems ✓ Programmable or non-programmable operation ✓ 7-day or 5+2 day programming, 2 or 4 events per day ✓ Touchscreen can be locked with varying levels of protection ✓ Adjustable cooling & heating limits ✓ Powered by battery or system voltage ✓ Optional sensor adds outdoor temp display or indoor temp averaging 	<ul style="list-style-type: none"> ● Input Voltage (Hardwired): 20-30 VAC 50/60 Hz ● Relay Rating: 24 VAC @ 1 Amp maximum per relay ● Battery Power: (2) AAA 1.5 V ● Operating Temperature: 32° F to 150° F ● Operating Relative Humidity: 0-95% (non-condensing) ● Storage Temperature: 32° F to 150° F ● Size: 5.0" W x 3.375" H x 1.0" D ● LCD Display Size: 3.75" W x 2.125" H ● Short-Cycle Delay: Off or 4 minutes ● Displayed Temperature Resolution: 1° F ● Setpoint Range: ● Heating 41° F - 120° F ● Cooling 43° F - 122° F ● Heating and Cooling Limits: Fully adjustable ● Onboard and Remote Sensors: NTC type 2 ● Resistance 10KΩ @ 77° F ● Tolerance +/- 3% @ 77° F
 <p>Part # - CE132</p>	<ul style="list-style-type: none"> ✓ Two-Stage ✓ Waterproof ✓ Corrosive Environment Thermostat ✓ Coiled, Tin-Plated Copper Tube Sensor Mounted on Side ✓ NEMA 4X enclosure ✓ Adjustable Dial ✓ Designed to Withstand Moisture and Gases found in Agricultural Buildings ✓ Ideal for long life in Livestock Confinement Buildings, Greenhouses, and Warehouses 	